

Datos técnicos JOHN DEERE 670G

CARDAN

Motor - marca John Deere

Motor - modelo PowerTech Plus 9.0L

Numero de cilindros 6

Desplazamiento, ltr (Inches³) 9 (548)

Potencia, kW (hp) 172 (230)

Peak Engine Torque, Nm (lbf / ft) 1204 (888)

Torque Rise, % 63

Transmision - marca John Deere

Number Of Speeds - Forward 8

Number Of Speeds - Reverse 8

Front Wheel Drive No

Axle Oscillation, ± ° 16

Front Wheel Lean, ± ° 20

Frenos de servicio - tipo Disc

Frenos de servicio - activación Hydraulic

DIMENSIONES

Longitud total, mm (ft/in) 8890 (29 ft 2 in)

Altura de la cabina con ROPS, mm (ft/in) 3180 (10 ft 5 in)

Transport Width, mm (inches) 2490 (98)

Distancia entre ejes, mm (ft/in) 6160 (20 ft 3 in)

Bladebase, mm (ft/in) 2570 (8 ft 5 in)

Moldboard Sideshift - Right, mm (inches) 683 (26.9)

Moldboard Sideshift - Left, mm (inches) 683 (26.9)

Shoulder Reach - Right, mm (ft/in) 2083 (6 ft 10 in)

Shoulder Reach - Left, mm (ft/in) 2083 (6 ft 10 in)

Circle Rotation, ° 360

Turning Radius - Minimum, m (ft/in) 7.21 (23 ft 8 in)

Frame Articulation, ± ° 22

PESOS

Operating Weight, kg (lbs) 15340 (33820)

Weight With Push Block & Ripper, kg (lbs) 18366 (40490)

Máximo peso de la máquina, kg (lbs) 24948 (55000)

